

# AGILE-QX-50 Assembly Guide



# 1. Install handle bar



tip: best to remove the front panel to gain better access with tool to install the handle bar bolt and nuts.

# 1-2. Handle bar cover





## 2. Install Rear Shock



## 3. Install Rear Shock



## 4. Install Side Kick Stand





## 5. Install Front Wheel



Tip: Remove brake caliper for easier installation on the front wheel, insert brake caliper after wheel is properly installed

## 6. Install Front Fender





## 7. Install Center Stand



## 8. Install Handle Bar End



tips: Push the handle bar in hard to engage and screw it the end screw to tighten it



## 9. Install Front upper small panel



tips: make sure to use the correct screw size, match the screw to the thread hole and make sure it is not too big for it and the panel itself it clip in along with screw to tighten it.



## 10. Install Muffler Heatshield



tips: Insert rubber first as shown in the picture and then insert the bolt with spacer on the back before installation



# 11. Install Passenger Foot Peg



## 12. Install Rear Carrier



Tips: use a pin size tool and a hammer to properly insert the pin full way





## 13. Install Rear View Mirror



Tips: to screw in the mirror, make sure to connect the thread properly and thread in. Once it reach to a position you like, lock it down with the bolt on the mirror turing it the opposite way to tighten it

## 14. Install Battery and Cover

