

DF200GSX Assembly Guide

This go-kart is suggested to assemble by professional mechanic only, Red Fox Powersports is not responsible for any damage or accident occur before or during operation by improper assembly.

1. Remove all outer cardboard box
2. Layout all parts
3. Install and charge the battery



4. Install Rear wheel





5. Install Front A-arm and Shock





6. Install Front Wheel
7. Install Driver Seat





8. Install Passenger Seat









9. Install Steering Wheel





10. Install Wheel Fender





11. Install Upper Roll Cage (insert Bolt and nuts loose only, DO NOT tighten yet)











www.redfoxpowersports.com



www.redfoxpowersports.com



www.redfoxpowersports.com



12. Install Front Carrier Rack (insert Bolt and nuts loose only, DO NOT tighten yet)









13. Install Rear Net





14. Install Rear Carrier Rack









15. Install Spare tire Rack











16. Install Roof







17. Tighten all roll cage bolt and nuts
18. Install Rear Engine Protection Plate





19. Install Seat Belt





20. Install Rear View Mirror





21. Locate Gas cap and add gas



22. Electric Start (step on brake pedal, pull choke lever and turn the key switch, once started release the choke lever)





23. Remote shut off (press lock button to remote shut off engine, press unlock button to enable start again, if you do not press the unlock button you will not able to start the go-kart)



24. Pull Start (Turn key switch, pull choke lever, locate Pull start lever, once started release the choke lever)

