

DF200GVS Assembly Guide

This go-kart is suggested to assemble by professional mechanic only, Red Fox Powersports is not responsible for any damage or accident occur before or during operation by improper assembly.

1. Remove all outer cardboard box
2. Layout all parts
3. Install and charge the battery (red positive, green negative)



4. Install Rear wheel



5. Install Front A-arm



6. Install Rear Suspension Shock





7. Install Front Wheel



8. Install Seats









9. Install Steering Wheel





10. Install Upper Roll Cage (insert Bolt and nuts loose only, DO NOT tighten yet)











www.redfoxpowersports.com



www.redfoxpowersports.com

11. Install Spare tire rack (insert Bolt and nuts loose only, DO NOT tighten yet)













12. Install Engine Protection Plate





13. Install Seat Belt





14. Install Rear Fender (The bracket needs to be adjusted on the frame first)









15. Install Front Fender







16. Install Spotlight Bar





17. Install Top Carrier





18. Install Spare Wheel







19. Tighten all roll cage bolts and nuts

20. Locate Gas cap and add gas





21. Remote shut off (press lock button to remote shut off engine, press unlock button to enable start again, if you do not press the unlock button you will not able to start the go-kart)





22. Pull Start (Turn the key switch, pull choke lever, locate Pull start lever, once started release the choke lever)





